



Specifications Noxion LED Panel Delta Pro V5 28W 3920lm - 840 Cool White | 60x60cm - UGR <19 - Sidelit - Dali Dimmable

[View Product](#)

## General Information

|                      |                                                                                             |
|----------------------|---------------------------------------------------------------------------------------------|
| SKU                  | 257870                                                                                      |
| EAN                  | 8719157073813                                                                               |
| Manufacturer Code    | 8719157073813                                                                               |
| Brand                | Noxion                                                                                      |
| Manufacturer Name    | Noxion LED Panel Delta Pro V5.1 28W 3920lm 4000K 600*600 UGR<19 Sidelit - DALI dimmable NDL |
| Budgetlight warranty | 6 Years                                                                                     |
| Average Lifetime (h) | 100000                                                                                      |
| Product Serie        | Delta Pro                                                                                   |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 28W                |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |

|                        |                   |
|------------------------|-------------------|
| Luminous Flux (Lumen)  | 3920lm            |
| Lumen per watt         | 140               |
| IP-rating              | IP20              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Fixture Connection     | Push Terminal     |
| Finish of Reflector    | Frosted           |
| Power factor           | >0.90             |
| Product Type Category  | LED Panel         |

## Fixture Information

|                       |                    |
|-----------------------|--------------------|
| Mounting Method       | Recessed           |
| Unified Glare Rating  | < 19 - For offices |
| Optical Cover         | PS (Polystyrene)   |
| Operating Temperature | -20 to +40         |
| Emergency Lighting    | No Emergency Unit  |
| Colour of the Fixture | White              |
| Housing               | Steel              |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 10      |

**Sensor Information**  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor



**Easy** return process

No Sensor



Long-life **LED solutions**